

Feature Matrix GL Logger Familien

The data loggers of the GL families are the optimal devices for logging CAN/CAN FD, LIN and FlexRay data communication. Additionally, the data loggers support the logging of analog measurement data like battery voltage as well as internal ECU parameters via diagnostics and CCP/XCP during a test drive. Due to its low current consumption in sleep mode, the data loggers are excellent for in-vehicle tests and use in test fleets.

Features	GL1000 GL1010	GL2000 GL2010 GL2400	GL3000 GL3100 GL3200	GL4000 GL4200	GL5350 GL5370
Logging Networks					
CAN channels	2	4	9	9	GL5350: 20 GL5370: 24
thereof CAN FD channels	-	GL2400: 4	-	-	GL5350: 4 GL5370: 12
LIN channels	2...16 ¹	2...16 ¹	2...16 ¹	2...16 ¹	6...16 ¹
FlexRay channels	-	-	-	2 ²	2 ²
RS232 interface	1	1	2	2	8
Data Storage					
SD/SDHC card ³	✓	✓	-	-	-
Compact Flash card ³	-	-	GL3000 GL3100	GL4000	-
Solid State Disk ³	-	-	GL3200	GL4200	✓
Data Transfer					
USB 2.0	✓	✓	✓	✓	✓
Memory card in card reader	✓	✓	GL3000 GL3100	GL4000	-
Solid State Disk via eSATAp	-	-	GL3200	GL4200	✓
Wi-Fi ³	-	-	✓	✓	✓
Cellular radio ³	-	✓	✓	✓	✓
Ethernet	-	-	✓	✓	✓
Cloud	-	✓	✓	✓	✓
Inputs, Outputs					
Digital inputs	2 ⁴	4 ⁴	8	8	4
Digital outputs	2 ⁴	4 ⁴	8	8	4
Analog inputs	4	4	6	6	6
Analog extension board ³	-	-	8	8	8
Keypad, Display					
LEDs (freely programmable)	4	4	5	5	5
Display	-	-	✓ ⁷	✓	✓
Event buttons	-	-	4 ⁷	4	4
Buttons on remote control	-	2	2	2	2
Additional Hardware Features					
Real-time clock with battery	✓	✓	✓	✓	✓

Features	GL1000 GL1010	GL2000 GL2010 GL2400	GL3000 GL3100 GL3200	GL4000 GL4200	GL5350 GL5370
Beep	✓	✓	✓	✓	✓
IP65 variant	GL1010	GL2010	-	-	-

Features	GL1000 GL1010	GL2000 GL2010 GL2400	GL3000 GL3100 GL3200	GL4000 GL4200	GL5350 GL5370
Sleep/Wake-Up Features⁵					
Sleep mode	✓	✓	✓	✓	✓
Standby mode with fast wake-up	-	✓	✓	✓	✓
Wake-up over CAN, LIN, wake line and clock	✓	✓	✓	✓	✓
Logging Functions					
Message oriented logging	✓	✓	✓	✓	✓
Signal oriented logging	✓	✓	✓	✓	✓
Permanent logging	✓	✓	✓	✓	✓
Trigger on messages, signals	✓	✓	✓	✓	✓
Trigger with pre-/post-trigger time	✓	✓	✓	✓	✓
Filter for data reduction	✓	✓	✓	✓	✓
Logging digital inputs and outputs	✓	✓	✓	✓	✓
Logging analog inputs	✓	✓	✓	✓	✓
Transmit CAN messages	✓	✓	✓	✓	✓
Timer, Timeout	✓	✓	✓	✓	✓
CCP/XCP on CAN with Seed & Key ^{3,6}	✓	✓	✓	✓	✓
XCP on FlexRay with Seed & Key ^{3,6}	-	-	-	✓	✓
XCP on Ethernet with VX modules ³ , CSM modules ³	-	-	✓	✓	✓
Diagnostics over UDS, KWP2000 on CAN, OBD II	✓	✓	✓	✓	✓
Online classification	-	✓	✓	✓	✓
Rainflow analysis	-	✓	✓	✓	✓
Drive recorder function	-	✓	✓	✓	✓
Monitoring Interface	-	✓	✓	✓	✓
Data Analysis					
Data formats BLF, ASC, MDF, MAT, HDF, ADTF, TXT	✓	✓	✓	✓	✓
Offline analysis with CANoe, CANalyzer	✓	✓	✓	✓	✓
Offline analysis with CANape, vSignalizer	✓	✓	✓	✓	✓
MS Excel	✓	✓	✓	✓	✓
Extensions					
CANgps ³ – log GPS position	✓	✓	✓	✓	✓
LINprobe ³ – additional LIN channels	✓	✓	✓	✓	✓
LOGview ³ – display for information	✓	✓	✓	✓	✓
HostCAM ³ /F44 with lenses ³ – digital cameras	-/-	-/-	✓/-	✓/-	✓/✓
CAS1T3L ³ – remote control	-	✓	✓	✓	✓
CASM2T3L ³ – speech recording	-	✓	✓	✓	✓
VoCAN ³ – speech recording and speech output	-	✓	✓	✓	✓
VX modules ³ – fast ECU measurement	-	-	✓	✓	✓
CSM CAN/EtherCAT® modules ³ – enhanced measurement technology	✓/-	✓/-	✓/✓	✓/✓	✓/✓

Features	GL1000 GL1010	GL2000 GL2010 GL2400	GL3000 GL3100 GL3200	GL4000 GL4200	GL5350 GL5370
Wi-Fi ³ / Cellular radio ³ – wireless data transfer	-/-	-/✓	✓/✓	✓/✓	✓/✓

Legend: ✓ = Available - = Unavailable

- 1

LINprobe required expanding to 16 LIN channels
- 6

CANape required for
- Seed & Key
- 2

2 FlexRay channels equal to 1 cluster
- 7

Not for GL3000
- 3

Additional product, not included in standard delivery
- 4

Alternatively as digital input or output
- 5

Wake-up capable CAN transceiver required